

Connection tools For wrapped and IDC connections

The connection tools are the essential complements for the connection of conductors. In order to achieve reliable connections, it is necessary to use tools which are suitable for the type of contact and the diameter of the conductors used,

- Ease of use,
- No requirement for outside power

Tools for wrapped connections :

These tools are used to make the connections on products fitted with wrapped connections.

The range offered is used to connect wires from 0.4 to 0.8 mm in diameter.

In the case of small installations with a small number of connections, manual wrappers and unwrappers are the most suitable.

For larger installations however, use of the manual wrapping gun, equipped with guides and of pins suitable for the diameter of the wires to be connected, reduces the connection time.



Connection tools for wrapped connections

OSA 2 tool for IDC contacts (Except COMPAX, DTI, DH8) :

It must be used for the insertion or the extraction of the wires on IDC contacts.

The OSA 2 tool, is used for connection of conductors with diameters between 0.4 and 0.8 mm, with or without automatic cutting of the wire. For disconnection of the wires, an extractor is available on the handle of the tool.

OSA 3 tool for IDC contacts :

It has the same functionalities than OSA 2 but is used for connection of conductors with diameters between 0.32 and 0.9 mm, with or without automatic cutting of the wire. It must be used to wire the products of the COMPAX, DTI and DH8 ranges.



Connection tools for IDC connections

References :

Description	Part No.	Pack.
Wire wrapping tool, 0.4 mm	55266	1
Wire wrapping tool, 0.5 and 0.6 mm	55267	1
Wire wrapping tool, 0.8 mm	55269	1
Wire wrapping tool, 0.4 to 0.8 mm	55270	1
Manual wrapping gun	55140	1
Wire wrapper pin, 0.4 mm	55146	1
Wire wrapper pin, 0.5 to 0.6 mm	55145	1
Wire wrapper pin, 0.8 mm	55144	1
Wire wrapper pin, 0.4 to 0.8mm	55264	1
Wire guide 0.4 to 0.5 mm	55149	1
Wire guide 0.5 to 0.6 mm	55148	1
Wire guide 0.8 mm	55147	1
Wrapper wire guide	55265	1
OSA 2 tool (except COMPAX, DTI, DH8 ranges)	06014	1
OSA 3 tool (For all products)	93417	1



Nexans Interface

35, rue Jean Jaurès BP 62 - 95872 BEZONS Cedex - France
Phone : +33 (0)1 39 96 56 56 - Fax : +33 (0)1 39 96 56 53
www.nexans.com